

水上娱乐及卫浴 解决方案



亚什兰



ashland.com / efficacy usability allure integrity profitability™

水上娱乐及卫浴 Aqua Recreation and Sanitary

	名称 Name	特性和应用领域 Characteristics and Applications
胶衣 Gelcoat	间苯新戊二醇型胶衣 MAXGUARD™ GN XXXXXX S	优异的耐候性和耐水性能，耐热高，适合高档的卫浴产品 Premium gelcoat, excellent UV resistance and hydrolysis resistance, high HDT, for premium sanitary wares.
	抗 UV 间苯新戊二醇型胶衣 MAXGUARD™ SX XXXXXX S	杰出的耐候性，耐水性能和保光性能，耐热高，适合高档的卫浴产品。 Premium gelcoat, excellent UV resistance and hydrolysis resistance, excellent gloss retention, high HDT, for premium sanitary wares.
	间苯新戊二醇型胶衣 MAXGUARD™ SW XXXXXX S	优异的耐候性和耐水性能，耐活性氯，适合小型游泳池 Premium gelcoat, excellent UV resistance and hydrolysis resistance, anti chlorine, for small swimming pools.
	间苯新戊二醇型胶衣 MAXGUARD™ GN XXXXXX SBR	优异的耐候性和耐水性能，耐热高，耐遇水泛白，适合户外水上游乐设施。 Premium gelcoat, excellent UV resistance and hydrolysis resistance, blushing resistance, high HDT, for water slides.
	间苯新戊二醇型胶衣 MAXGUARD™ GNJ XXXXXX S	低苯乙烯挥发技术，耐候性和耐水性能好，硬度高，光泽好，操作性好，适合高档的卫浴产品 Low styrene emission gelcoat, good UV resistance and hydrolysis resistance, high hardness and good glossy, easy application, for premium sanitary wares.
	间苯新戊二醇型胶衣 MAXGUARD™ GS XXXXXX S	优异的耐候性和耐水性能，耐热高，操作性好，适合高档的卫浴产品 Premium gelcoat, excellent UV resistance and hydrolysis resistance, high HDT, easy application, for premium sanitary wares.
	间苯型胶衣 ENGUARD™ GE XXXXXX S/H	良好的耐候性和耐水性，适合通用卫生洁具。 Good UV resistance and hydrolysis resistance for general sanitary wares.
树脂 Resin	邻苯型浇注树脂 AROPOL™ S 380 series resin Ortho Solid Surface	非触变、预促进，高活性邻苯型浇注树脂，具有较高的机械性能和表面硬度，可添加高含量填料；特别推荐用于具有高强度人造石、实体面材、有色颗粒及聚酯混凝土制品。 Non-Thixotropic, pre-accelerated casting resin of high reactivity. High filler loading. It is especially recommended for high strength culture marble, solid surface and polyester concrete.
	亚克力粘接树脂 AROPOL™ AF 50402 series resin Acrylic Bonding Resin	触变、预促进，快固化亚克力粘接树脂，具有优秀的机械性能和粘接性能，可添加高含量填料；特别推荐用于亚克力浴缸，SPA 缸和小型泳池制作。 Thixotropic, pre-accelerated acrylic bonding resin, excellent adhesion to acrylic sheet and mechanical properties and fast cure with high filler loading. It is especially recommended for acrylic bath tubs, SPA tubs and acrylic swimming pools.
	低苯乙烯挥发树脂 AROPOL™ M105 series Low Styrene Emission Resin	邻苯型低挥发通用树脂，采用手糊和喷射工艺制造常用复合材料部件。 Low emission resin, suitable for spray-up and hand lay-up processes for fabricating composite structure.
	间苯型树脂 AROPOL™ K530TB Iso Hand Lay-up Resin	触变，预促进间苯型手糊 / 喷射树脂，较好的耐水性能，英国劳氏船级社认证。 Thixotropic, pre-accelerated, isophthalic resin for hand lay-up and spray-up, good water resistance, Lloyds certificate.

亚什兰（中国）投资有限公司

亚什兰复合材料

上海市中山南二路 1089 号

徐汇苑大厦 18 层，200030

电话：+86 21 2402 4880

电邮：apmasiacustomerservice@shland.com

www.ashlandchina.com

